

T7

For excavators 5.0-8.0 ton



MZ



HF3
Ø max 8 cm
**STANDARD
EQUIPMENT**



KF3
Ø max 6 cm

		T7 105	T7 125
	ton	5.0-8.0	6.0-8.0
	cm/inch	105 42	125 50
	cm/inch	125x75x50 50x30x20	145x75x50 58x30x20
	kg/lbs	220 485	250 551
	cc	22-27-34	22-27-34
	oil - L/min (gal/min)	60-70-80 16-19-22	60-70-80 16-19-22
	bar/psi (min-max)	200-220 2.900-3.200	200-220 2.900-3.200
	transmission	direct	direct
	rotor diameter cm/inch	36 14	36 14
		16	20

Technical features and standard equipment

- Direct transmission
- Internally reinforced with double metal sheet
- Feeler roller adjustable on 3 positions to change the height of the cut
- Helicoidal rotor with austempered hammers or blade interchangeable
- Protective cover for motor
- Inside rotor supports with labyrinth for the protection of the bearings from the impurities
- Double row spherical adjustable bearings of 1st quality
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation
- Cast iron gear motor
- Accident prevention rubber protections according to EC directives

Accessories

- Mounting hitch (pins version)
- Pins kit
- Quick hitch
- Hoses kit Lg. 2 meters
- Self-levelling support (+40kg)
- Hydraulic rotation device (no self-levelling support)
- Valves block deduction, only anticavitation

Cast iron hydraulic gear motor range

	ton	5-7	7-8	8-9
	cc	22	27	34
	oil - L/min gal/min	60 16	70 19	80 22